✓ STORM|AUDIO

PA MK3 - SPECIFICATIONS

| | | | PA 16 MK3 | PA 8 MK3 ULTRA | |
|------------------------|--|--|---------------------|--|-------------------|
| Main Features | Control | Power status (Button ON/OFF) | \checkmark | \checkmark | |
| | oona of | Power indication (LED, red / green) | \checkmark | \checkmark | |
| | Protection | Overheat | \checkmark | \checkmark | |
| | (Blinking LED) | Overcurrent | \checkmark | \checkmark \checkmark \checkmark | |
| | | Overlvoltage | \checkmark | | |
| | | DC error | \checkmark | | |
| | Power up | Trigger control or front button | \checkmark | | |
| | Electronically controlled ventilation | Using several thermal sensors | \checkmark | \checkmark | |
| Connectivity | Analog inputs | XLR | \checkmark | \checkmark | |
| | | RCA | N/A | N/A | |
| | Ethernet | Connected to network (DHCP or static IP) | \checkmark | \checkmark | |
| | Trigger in, Trigger out | (daisy chain with electronic delay) | \checkmark | \checkmark | |
| Remote monitoring | | Serial number settable 🗸 | | \checkmark | |
| via ISP processor user | | IP address | \checkmark | \checkmark | |
| interface | | Amplifier model | \checkmark | \checkmark | |
| | | Temperature | \checkmark | \checkmark | |
| | | Fan speed | \checkmark | \checkmark | |
| | | Power status and control | \checkmark | \checkmark | |
| | | Mute status | \checkmark | \checkmark | |
| | | Protection / malfunction | \checkmark | \checkmark | |
| Specifications | Amplifier class | Pascal Audio | Class D | Class D | |
| | Channel configuration | | SE - 16 | SE - 8 (Normal) | BTL - 4 (Bridged) |
| | Output power | RMS 8 Ω : 1 kHz 0.1% distortion | 200 W | 200W | 800 W |
| | 2 channels driven | RMS 8 Ω : 1 kHz 1% distortion | 250 W | 250 W | 1000 W |
| | | RMS 4 Ω : 1 kHz 0.1% distortion | 400 W | 400 W | 900 W |
| | | RMS 4 Ω : 1 kHz 1% distortion | 490 W | 490 W | 1100 W |
| | Output power | RMS 8 \wp : 20 Hz - 20 kHz 0.1% distortion | 200 W | 200 W | 800 W |
| | All channels driven | RMS 4 \wp : 20 Hz - 20 kHz 0.1% distortion | 225 W | 400 W | 800 W |
| | Frequency response | High : -3 dB CEM | 50 kHz | 50 kHz | 50 kHz |
| | | Low : - 3 dB CEM | 10 Hz | 10 Hz | 10 Hz |
| | Signal / Noise ratio (Bandwidth : 20 kHz) | Reffered to P-rated | > 115 dB | > 115 dB | > 115 dB |
| | THD (20Hz-20kHz), 1 Watt to -1dB max.power | | < 0,03% | < 0,03% | < 0,03% |
| | Gain | Standard | 26 dB | 26 dB | 32 dB |
| | Damping factor | | > 400 | > 400 | |
| | Fan noise (max.) | | < 30 dB | < 30 dB | |
| Power Supply | | Voltage range | 100V to 240V | 100 to 240V | |
| | | Туре | Switching mode | Switching mode | |
| | | Power supply capacity | 3200W | 3200W (ultra high current) | |
| | | Range selection | Universal | Universal | |
| Casing | | Home / rack | $\sqrt{\sqrt{2}}$ | \checkmark/\checkmark | |
| | | Gross weight (kg) | 25,00 | 25,00 | |
| | | Net weight (kg) | 21,00 | 21,00 | |
| | | Size | 3RU | 3RU | |
| | | Dimensions - no ears, no feet, connectors included (cm) | 49,1 x 44,2 x 13,27 | 49,1 x 44,2 x 13,27 | |
| | | <i>Ears : +4 cm (2 x 2 cm) - Feet : + 2 cm</i> Dimensions - with box (cm) | 67 x 63 x 30 | 67 x 63 x 30 | |
| | | | | | |

All trademarks are the property of their respective owners. The information and product specifications contained in this datasheet are subject to change at any time without notice. StormAudio accepts no liability or responsability for any errors or omissions in the information on this datasheet or for damages from relying on the content of this datasheet.